


Welding Generator Sets

Series GS/DS



ENGINES

Petrol: 4 stroke air cooled 3000 r.p.m. Electronic start, on-head valves (OHV). Automatic decompressor for start-up. Manual self-recoiling starter rope or electric start.

Diesel: 4 stroke air cooled 3000 r.p.m. Direct injection and lubrication via gear driven pump. Electric start, battery included.

ALTERNATOR

Synchronous, self-regulating and self-ventilating. Auxiliary 220 V single phase socket and 380 V three phase socket (except GS 170). Alternator includes voltmeter (except GS 180 and GS 200) and thermal circuit breaker, plus output sockets. For 240 A welding set, panel equipped with three phase/single phase circuit breaker, voltmeter and hours run meter.

The welding sets of the series GS/DS are ideally suited for rough environmental applications.

- Engine and alternator are mounted on tubular chassis with anti-vibration dampers.
- All gensets are supplied with wheels and handle.
- Pincers and cables (3m of welding cable and 2m of ground cable) are Included.
- Larger power levels on request

PETROL WELDING SETS

	WELD. OUTPUT	ENGINE		ELEC TRODE	AUX. OUTPUT		DIMEN SIONS			WEIGHT
MODEL PS	A	Manu- facturer	h.p.	mm	single phase kVA	three phase kVA	Width mm	Depth mm	Height mm	kg
GS 170 H	170	Honda	9	3.25	5	-	835	625	600	70
GS 170 V	170	Vanguard	9	3.25	5	-	835	625	600	70
GS 180 H	180	Honda	13	4	2.5	5	835	625	600	95
GS 200 H	200	Honda	13	4.5	2.5	5	935	625	595	110
GS 200 V	200	Vanguard	14	4.5	2.5	5	935	645	735	140
GS 240 V	240	Vanguard	16	5	4	9	960	645	690	140

DIESEL WELDING SETS

	WELD. OUTPUT	ENGINE		ELEC- TRODE	AUX. OUTPUT		DIMEN- SIONS			WEIGHT
MODEL PS	A	Manu- facturer	h.p.	mm	single phase kVA	three phase kVA	Width mm	Depth mm	Height mm	kg
DS 170 L	170	Lombardini	9	3.25 mm	5	-	835	645	645	110
DS 240 L	240	Lombardini	12	5 mm	4	9	1040	760	780	160

... WHERE THE POWER COMES FROM ...